

GUIDE 313

Cut protection glove with nitrile

This soft glove combines comfort with high durability and good protection against sharp objects. The foam nitrile coating is naturally free from DMF. It is also breathable which helps to keep the wearer's hands cool throughout the day.

Suitable for construction work, sheet metal assembly, automotive, recycling, and material handling.




DURABILITY



FLEXIBILITY

- Cut protection level D
- Seamless in HDPE/glass fibre
- Cool and ventilating
- Sizes 7-12



ARTICLE NUMBER	SIZE
223546463	7
223546464	8
223546465	9
223546466	10
223546467	11
223546468	12

MEASUREMENTS	SIZE 7 (S)	SIZE 8 (M)	SIZE 9 (L)	SIZE 10 (XL)	SIZE 11 (XXL)	SIZE 12 (XXXL)
Total glove length (+/- 5 mm)	235	240	249	265	271	280
Palm width (+/- 5 mm)	82	85	90	92	95	95
Glove weight/pair (+/- 5 grams)	59	60	69	72	80	85
Over lock colour	Orange	White	Yellow	Black	Green	Brown
Wrist length	80	80	85	85	85	95
Wrist width	80	80	88	90	90	90

TEST RESULT	NOTIFIED BODY	SCORE / PASS
EN 420:2003 + A1: 2009	0403 Finnish Institute of Occupational Health	Pass
EN 388:2016	0403 Finnish Institute of Occupational Health	4X43D

PERFORMANCE LEVEL EN 388:2016

EN 388 - Abrasion resistance (nr. of cycles)	8000 (4)
EN 388 - Cut resistance, coup test (index)	n/a (X)
EN 388 - Tearing resistance (N)	75 (4)
EN 388 - Puncture resistance (N)	100 (3)
EN 388 - Cut resistance, TDM ISO 13977 (N)	15 (D)

PERFORMANCE LEVEL EN 420:2003

EN 420 - Dexterity	Level 4
EN 420 - pH	Pass
EN 420 - Azo colourants	Pass