

GUIDE 574

Thin working glove with nitrile

The seamless nylon knitting provides an excellent fit and good sensitivity at the fingertips. Palm dipped with microporous nitrile with excellent ventilation. The cuff has a tight fit around the wrist. A glove with high dexterity and excellent comfort.

Suitable for construction work and assembly.



DURABILITY



FLEXIBILITY



- Seamless in nylon
- Tight fit
- Good breathability
- Good grip
- Sizes 6-12



ARTICLE NUMBER	SIZE
223546602	6
223546603	7
223546604	8
223546605	9
223546606	10
223546607	11
223546608	12

MEASUREMENTS	SIZE 6 (XS)	SIZE 7 (S)	SIZE 8 (M)	SIZE 9 (L)	SIZE 10 (XL)	SIZE 11 (XXL)	SIZE 12 (XXXL)
Total glove length (+/- 5 mm)	200	207	215	230	235	250	253
Palm width (+/- 5 mm)	71	75	82	85	90	93	98
Glove weight/pair (+/- 5 grams)	28	30	31	34	38	42	45
Over lock colour	Red	Orange	White	Green	Black	Green	Black
Wrist length	65	72	73	78	80	85	-
Wrist width	72	73	80	80	85	85	-

TEST RESULT	NOTIFIED BODY	SCORE / PASS
EN 420:2003 + A1: 2009	0403 Finnish Institute of Occupational Health	Pass
EN 388:2016	0403 Finnish Institute of Occupational Health	4121X

PERFORMANCE LEVEL EN 388:2016

EN 388 - Abrasion resistance (nr. of cycles)	8000 (4)
EN 388 - Cut resistance, coup test (index)	1.2 (1)
EN 388 - Tearing resistance (N)	25 (2)
EN 388 - Puncture resistance (N)	20 (1)
EN 388 - Cut resistance, TDM ISO 13977 (N)	n/a (X)

PERFORMANCE LEVEL EN 420:2003

EN 420 - Dexterity	Level 5
EN 420 - pH	Pass
EN 420 - Azo colourants	Pass