

GUIDE 577

Thin working glove with nitrile

The seamless nylon knitting provides an excellent fit and good sensitivity at the finger tips. Palm dipped with microporous nitrile with excellent ventilation. The cuff has a tight fit around the wrist. A glove with high durability and excellent comfort.

Suitable for construction work and assembly.



DURABILITY



FLEXIBILITY



OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
15.HCN.70502 HOHENSTEIN HTTI
Tested for harmful substances.
www.oeko-tex.com/standard100

- Seamless in nylon
- Tight fit
- Good breathability
- Good grip
- Sizes 6-12



EN 388
4131X

ARTICLE NUMBER	SIZE
223546572	6
223546573	7
223546574	8
223546575	9
223546576	10
223546577	11
223546578	12

MEASUREMENTS	SIZE 6 (XS)	SIZE 7 (S)	SIZE 8 (M)	SIZE 9 (L)	SIZE 10 (XL)	SIZE 11 (XXL)	SIZE 12 (XXXL)
Total glove length (+/- 5 mm)	215	225	235	245	255	265	275
Palm width (+/- 5 mm)	79	82	89	92	98	102	107
Glove weight/pair (+/- 5 grams)	28	30	34	37	40	42	62
Over lock colour	Red	Orange	White	Yellow	Black	Green	Brown
Wrist length	55	70	75	75	80	80	80
Wrist width	70	75	77	80	85	85	85

TEST RESULT	NOTIFIED BODY	SCORE / PASS
EN 420:2003 + A1: 2009	0403 Finnish Institute of Occupational Health	Pass
EN 388:2016	0403 Finnish Institute of Occupational Health	4131X

PERFORMANCE LEVEL EN 388:2016	
EN 388 - Abrasion resistance (nr. of cycles)	8000 (4)
EN 388 - Cut resistance, coup test (index)	1.2 (1)
EN 388 - Tearing resistance (N)	50 (3)
EN 388 - Puncture resistance (N)	20 (1)
EN 388 - Cut resistance, TDM ISO 13977 (N)	n/a (X)

PERFORMANCE LEVEL EN 420:2003	
EN 420 - Dexterity	Level 5
EN 420 - pH	Pass
EN 420 - Azo colourants	Pass