

GUIDE 662W

Winter lined glove with nitrile

A warm, soft and comfortable glove with a breathable two-layer insulated liner. Ideal for cold conditions while retaining excellent flexibility.

Suitable for mechanics, oil and gas industry and construction work.



DURABILITY



FLEXIBILITY



- Seamless in polyester
- Fully lined with acrylic
- Knuckle dipped
- Good grip
- Sizes 8-12



| ARTICLE NUMBER | SIZE |
|----------------|------|
| 223546654 | 8 |
| 223546655 | 9 |
| 223546656 | 10 |
| 223546657 | 11 |
| 223546658 | 12 |

| MEASUREMENTS | SIZE 8 (M) | SIZE 9 (L) | SIZE 10 (XL) | SIZE 11 (XXL) | SIZE 12 (XXXL) |
|---------------------------------|------------|------------|--------------|---------------|----------------|
| Total glove length (+/- 5 mm) | 240 | 255 | 265 | 275 | 285 |
| Palm width (+/- 5 mm) | 95 | 105 | 110 | 115 | 120 |
| Wrist length | 90 | 90 | 90 | 95 | 100 |
| Wrist width | 80 | 85 | 85 | 90 | 95 |
| Glove weight/pair (+/- 5 grams) | 90 | 100 | 110 | 150 | 153 |
| Edging colour | White | Yellow | Black | Green | Brown |

| TEST RESULT | NOTIFIED BODY | SCORE / PASS |
|------------------------|---|--------------|
| EN 420:2003 + A1: 2009 | 0403 Finnish Institute of Occupational Health | Pass |
| EN 388:2016 | 0403 Finnish Institute of Occupational Health | 4231X |
| EN 511:2006 | 0403 Finnish Institute of Occupational Health | X2X |
| EN 407:2004 | 0403 Finnish Institute of Occupational Health | X2XXXX |

PERFORMANCE LEVEL EN 388:2016

| | |
|--|----------|
| EN 388 - Abrasion resistance (nr. of cycles) | 8000 (4) |
| EN 388 - Cut resistance, coup test (index) | 2,5 (2) |
| EN 388 - Tearing resistance (N) | 50 (3) |
| EN 388 - Puncture resistance (N) | 20 (1) |
| EN 388 - Cut resistance, TDM ISO 13977 (N) | n/a (X) |

PERFORMANCE LEVEL EN 420:2003, EN 511:2006, EN 407:2004

| | |
|---|---------|
| EN 420 - Dexterity | Level 4 |
| EN 420 - pH | Pass |
| EN 420 - Azo colourants | Pass |
| EN 511 - Contact cold (Thermal resistance) (m² K/W) (minimum) | 0,050 |
| EN 511 - Flexibility (No crack after 10.000 cycles) | Pass |
| EN 407 - Contact heat (°C) | 250 |